

Plastic coated metal plate prodn., used for printed circuit board - by coating metal plate with pulverised fine powder of synthetic resin and inorganic filler using electrostatic technique

Patent Assignee: MITSUBISHI PLASTICS IND LTD (MISD)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 4367763	A	19921221	JP 91169458	A	19910614	199306 B

Priority Applications (No Type Date): JP 91169458 A 19910614

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 4367763	A	3	B05D-001/06	

Abstract (Basic): JP 4367763 A

Synthetic resin and inorganic filler are mixed; the mixt. pulverised into fine powders and the fine powders coated over a metal plate to form an insulating layer by an electrostatic coating technique. Opt. a metal foil or another metal plate is put on the insulating layer and the whole assembly heated and pressed to produce a laminated plate.

Pref. a metal plate of Al, Cu, Zn, Fe, silicon steel or Fe-Ni alloy 0.2-0.5 mm thick is used. Polysulphone, polyphenylene sulphide, polyether etherketone, thermoplastic fluoro-resin, polyetherimide, epoxy resin, or polyimide resin is used for the coating layer, 50-300 microns thick. Inorganic fillers of silicon, aluminium or boron nitride of 0.1-10 microns dia. are pref. used.

USE/ADVANTAGE - Used to produce a metal plate with a synthetic resin coating. The resultant laminated plate has a good heat conductivity and is used as a baseplate for a printed circuit board.

Dwg.0/0

Title Terms: PLASTIC; COATING; METAL; PLATE; PRODUCE; PRINT; CIRCUIT; BOARD
; COATING; METAL; PLATE; PULVERISE; FINE; POWDER; SYNTHETIC; RESIN;
INORGANIC; FILL; ELECTROSTATIC; TECHNIQUE

Index Terms/Additional Words: PCB

Derwent Class: A32; A85; L03; P42; P73

International Patent Class (Main): B05D-001/06

International Patent Class (Additional): B05D-007/14; B05D-007/24;
B32B-015/08; B32B-015/16; B32B-027/20; B32B-031/20

File Segment: CPI; EngPI

?